

GRID-TIE SOLAR SYSTEM

Challenger Series

MODEL NUMBER **020-A-GTP**

COMPONENT DATA

SOLAR PANELS

MAKE / MODEL	Q Cell / Q.Tron XL-G2.3 / BFG 630W
WATTAGE (STC / BSTC)	630 STC
TOTAL NUMBER OF PANELS	20

INVERTER

MAKE / MODEL	Fronius / Primo 12.5-1
MAX. ALLOWABLE DC INPUT VOLTAGE / CURRENT (FROM PV)	600 Volt / 51 Amp
MAXIMUM AC OUTPUT WITH GRID CONNECTION	12.5 kW
CONTINUOUS AC OUTPUT WITHOUT GRID CONNECTION	N/A
NUMBER OF INVERTERS	1
AC VOLTAGE / PHASE / FREQUENCY	240 Volts / Split Phase / 60 Hz
DC VOLTAGE TO BATTERIES	N/A
RECOMMENDED OPERATING TEMPERATURE RANGE	-40 to +140 Deg. F -40 to +60 Deg. C

ASSEMBLED SYSTEM ELECTRICAL DATA

COMPLETE SYSTEM

RATED DC POWER	12.60 kW
DC VOLTAGE / CURRENT (COMBINED STRINGS)	479 Volts / 29.1 Amps
MAXIMUM AC OUTPUT WITH GRID CONNECTION	12.5 kW
CONTINUOUS AC OUTPUT WITHOUT GRID CONNECTION	N/A
AC VOLTAGE / MAX CURRENT (COMBINED INVERTERS, IF APPLICABLE)	240 Volts @ 52.1 Amps
PHASE / FREQUENCY	Split Phase / 60 Hz

Challenger Series

Ph. 719-759-5100

www.SolarSet.com